

Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

Section 1.0 Identification of the substance / mixture and of the company

1.1 Product Identifier

Product Name : Zircocem 1 HSN Code : 3816 0000

Physical state : Powder / Liquid

Formula : NA Synonyms : NA

Chemical family : Inorganic Silicate

1.2 Recommended use of the substance/mixture and restrictions on use

Recommended use : High Temperature Adhesive for Refractory and Ceramic

Non-isolated Intermediate

For research and industrial use only

1.3 Details of the supplier of the safety data sheet

Jyoti Ceramic Industries Pvt Ltd C-21, N.I.C.E, Satpur Nashik Maharashtra India Tel +91-253-2350120/2351251; Fax +91-253-2350023

www.jyoticeramic.com

E-mail: info@jyoticeramic.com

For EU member states:

EC REP

Jyoti Ceramic GmbH

Frankenstr. 12, 90762 Fürth, Germany

Tel: +49 911 7871 2084; Fax +49 911 7871 2082

E-Mail: sales@jyoticeramic.com

1.4 Emergency Telephone Number

Jyoti Ceramic Industries Pvt Ltd

+ 91-253-2350120

Reachable during office hours (Indian Standard time):Sunday - Friday: 9.00 AM - 5.00 PM

Jyoti Ceramic GmbH

+49 911 7871 2084;

Reachable during office hours (Central European time): Monday - Friday: 8.30 AM - 5.00 PM



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

Section 2.0 Hazard(s) identification

2.1 Classification of the substance or mixture:

H290 : May be corrosive to metals

H301: Toxic if swallowed H315: Causes skin irritation

H318 : Causes serious eye damage
H319 : Causes serious eye irritation
H335 : May cause respiratory irritation

Precautionary: Prevention P264, P265, P270, 280

Precautionary: Response

P301, P302, P304, P305, P316, P317, P319, P321, P330, P332, P338, P340, P352,

P354, P362+P364

2.2 Label elements

2.3 Hazards not otherwise classified (HNOC) : No additional information available

Section 3.0 Composition / Information on Ingredients

3.1 Substance : Not Applicable

3.2 Mixture

Name : Not available CAS No. : Not available

Name of	CAS No	EINECS No	Wt %	GHS	REACH Reg.	
ingredient				classification		
PART 1: POWDER						
Zirconium Silicate	14940-68-2	239-019-6	> 75	Not classified		
Additive*			< 20	H301		
Quartz	14808-60-7	238-878-4	< 10	Not classified		
PART 2: LIQUID						
Potassium	1312-76-1	215-199-1	100	H290	01-2119456888	
Silicate				H315		
				H318		
				H319		
				H335		

^{*}The chemical identity is withheld because it is trade secret information of Jyoti Ceramic Industries

Full text of hazard classes and H-statement : see section 15



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

Section 4.0 Description of First Aid measures

4.1 Description of first aid measures

General : Remove contaminated clothing and shoes. In case of accident or if

you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; If not available show

packaging or label.

After inhaled : In case there symptoms of cough or shortness of breath,

move from exposure to a well ventilated place, and if breathing

difficulty occurs then consult a physician.

After skin contact : If irritation to skin occurs wash the

affected area with fresh and clean water.

After eye contact : If irritation occurs flush the eyes with fresh clean running tap

water. Get medical attention if irritation continues.

After Ingestion : If substantial quantity is swallowed, dilute with large

amount of water, then consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

Product and Product dust generated through handling, grinding, sanding or machining may cause irritation to the mucous membrane, eyes, skin and respiratory organs.

Symptoms/injuries after inhalation : May cause irritation
Symptoms/injuries after skin contact : May cause skin irritation
Symptoms/injuries after eye contact : May cause eye irritation
Symptoms/injuries after ingestion : May cause irritation

4.3 Indication of any immediate medical attention and special treatment method

No additional information available

> Section 5.0 Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Product is not combustible and non explosive.

Use a suitable extinguishing media for the

surrounding fire

Unsuitable extinguishing media : None known

5.2 Special hazards arising from the substrate or mixture

Fire hazard : None known

5.3 Advice for firefighters



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

Protection during firefighting : Do not enter fire area without proper protective

equipment, including respiratory protection.

Avoid contact with skin and eyes. Do not breathe

dust.

Section 6.0 Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Protective equipment : Wear protective equipment as described in

Section 8

Emergency procedures : Evacuate unnecessary and unprotected personnel.

Avoid formation of product dust

6.1.2 For emergency responders

Protective equipment : Do not attempt to take action without suitable

protective equipment. Equip clean-up crew with

proper protection.

Use protective clothing, dust mask, and eye protection. For further information refer to

section 8: "Exposure controls/personal protection".

6.2 Environmental precautions : Prevent entry of product into sewers and public

waters. Notify authorities if product enters sewers or

public waters.

6.3 Methods and material for contamination and cleaning up

For containment : Prevent migration and entry into sewers or streams

Methods for cleaning up : Collect the pieces or dust by vacuum or mechanically

for disposal and land filling as per local regulations.

Avoid dust formation during cleaning.

6.4 Reference to other sections:

See Heading 8. Exposure controls and personal protection

Section 7.0 Handling and storage

7.1 Precautions for safe handling

Risk of slipping if the product is spilt on the floor. Use safety shoes while handling. Wear safety glasses for eye protection. Sweep up and recover into a container for reuse or disposal. If dust



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

is generated then wear personal protecting clothing including particle filter/dust mask and eye protection.

7.2 Hygiene Measures

Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.3 Conditions for safe storage, including any incompatibilities:

Storage conditions : Keep container tightly closed

Incompatible materials : Not known

Storage area : Material should be stored in well protected

dry place, in its original packing.

7.4 Specific end uses

See section 1.2

Section 8.0 Exposure controls and personal protection

8.1 Control parameters

Airbourne product dust generated through handling, grinding, or sanding may cause irritation to the mucous membrane, eyes, skin and respiratory organs. The limits of dust concentration (mg/m³) at the work-place have to be considered.

The general dust limit according to the TRGS 900, for dust which does not exhibit any mutagenic, carcinogenic, fibrogenic, allergising or toxic effect applies:

The OEL value for A dust (alveolar dust fraction) is 1.25 mg/m3 The OEL value for E dust (inhalable dust fraction) is 10 mg/m3

Zirconium Oxide (1314-23-4)*				
ACGIH	STEL (mg/m ³)	10 mg/m ³ Zr		
	TWA (mg/m ³)	5 mg/m ³ Zr		
OSHA	STEL (mg/m ³)	10 mg/m³ Zr		
	TWA (mg/m ³)	5 mg/m ³ Zr		
Silicon Dioxide (7631-86-9)**				
ACGIH	TWA (mg/m ³)	10 mg/m ³		
DFG	MAK(mg/m ³)	4 mg/m ³		

^{*}The values are for total dust containing no asbestos and < 1 % crystalline silica.

8.2 Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Suitable ventilation / dust extraction system must be used in the workplace or on the equipment.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye

Page 5 of 9



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

wash fountains and safety showers should be available in the immediate vicinity of any

potential exposure.

Hand protection : Neoprene or nitrile rubber gloves

Eye protection : Safety glasses / goggles

Skin and body protection : Wear suitable protective clothing. After work ensure

that skin is cleaned and hand care products are

used.

Respiratory protection : In case of dust exposure respiratory protection

equipment must be worn. FFP2/FFP3 dust masks

with particle filters are recommended.

Section 9.0 Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Part 1: Powder, Part 2: Liquid

Odour None

Melting point Part 1: >1800°C, Part 2: NA

Freezing point Not Applicable

Ignition point Non Flammable

Density (g/cc) Part 1: 1.1_(powder), Part 2: 1.5 g/cc Solubility in water Part 1: Non soluble, Part 2: Soluble PH Part 1: NA, Part 2: 12 - 14

Vapour Pressure Not Applicable

Viscosity Part 1: NA, Part 2: 300 cps

Vapour Density
Partition Co-efficient
Explosive Properties
Oxidising Properties
Not Applicable
Not Applicable
Not Applicable

9.2. Other information

No additional information available

Section 10.0 Stability and reactivity

10.1 Reactivity : Not known
10.2 Chemical stability : Stable
10.3 Possibility of hazardous reactions : Not known
10.4 Conditions to avoid : Not known

10.5 Incompatible materials : Avoid contact with acids, and acid vapors

JYOTI CERAMIC

SAFETY DATA SHEET According to Regulation (EC) No. 1907/2006 (REACH)

Zircocem-1

Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

10.6 Hazardous decomposition products: Not known

Section 11.0 Toxicological information

11.1 Information on the toxicological effects

Acute toxicity

Potassium Silicate

 Oral: LD50 (rat, female)
 > 5000 mg/kg bw

 Inhalation: LC50 (rat)
 > 2.06 g/m3

 dermal: LD50 (rat)
 > 5000 mg/kg bw

Skin corrosion/irritation

Potassium Silicate

Dermal: Long Term, DNEL, (Workers) 1.49 mg/kg bw/day

Serious eye damage/irritation : H318, H319

Respiratory or skin sensitization

Potassium Silicate

Inhalation: Long Term, DNEL (Workers) 5.61 mg/m³

Germ cell mutagenicity : Not classified

Carcinogenicity : No evidence of carcinogenic effect

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated exposure) : Not classified Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Product dust may cause Respiratory

irritation

Symptoms/injuries after skin contact : Product dust may cause skin irritation

Symptoms/injuries after eye contact : May cause eye irritation

Symptoms/injuries after ingestion : H301

> Section 12.0 Ecological information

If used properly, no environmental problems are anticipated. Do not empty the product or ground water or drains.

12.1 Toxicity :

Potassium Silicate

PNEC agua (freshwater) 7.5 mg/L

12.2 Persistence & Degradability : Not known 12.3 Bioaccumulative Potential : Not known

12.4 Mobility in soil

12.5 Results of PBT and vPvB assessment : Product does not contain PBT or vPvB

substances (see. REACH Annex XIII)

12.6 Other Adverse Effect

Effect on ozone layer : Not known

Effect on the global warming : No known effects from this product.



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

GWP mix comment : No known effects from this product.

Section 13.0 Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer

Waste disposal recommendations : Comply with local regulations. If approved, flush with

water to chemical sewer. For large quantities,

neutralize and landfill solids or flush neutral liquid to

sewer with plenty of water.

Ecology - waste materials : Avoid release to the environment

Section 14.0 Transport information

No dangerous goods as defined by ADR/RID/ADN/GGVSEB, ICAO/IATA, IMDG, USDOT

14.1 UN number : Not regulated for transport.

14.2 UN proper shipping name : Not applicable14.3 Transport hazard class(es) : Not applicable

14.4 Packing Group : Not applicable14.5 Environmental Hazards : Not applicable

14.6 Special Precautions for the user : See section 7 and 8

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

: Not applicable

> Section 15.0 Regulatory information

15.1.: Safety, health and environmental regulations/legislation specific for the substance or mixture

Classification or labelling applicable in accordance with Regulation (EC) No 1272/2008

H290 : May be corrosive to metals

H301: Toxic if swallowed H315: Causes skin irritation

H318 : Causes serious eye damage
H319 : Causes serious eye irritation
H335 : May cause respiratory irritation







None of the chemicals in this product are considered highly hazardous by OSHA.



Date of Printing: 10.04.2024 SDS/ZIRCOCEM-1/REV 3 Created: 10/04/2024

15.2.: Chemical safety assessment

A chemical safety assessment of the product or its components is not available.

Section 16.0 Other information

16.1.: Abbreviations and acronyms

REACH: Regulation on Registration, Evaluation, Authorisation and Restriction of Chemicals.

TWA: Time Weighted Average; OEL: Occupational exposure limit;

ACGIH: American Conference of Governmental Industrial Hygienists;

OSHA: Occupational Safety and Health Administration:

CAS No.: Chemical Abstract Service Registration Number;

EINECS: European Inventory of Existing Commercial Chemical Substances

GHS: The Globally Harmonized System of Classification and labelling;

IATA: International Air Transport Association;

DOT: Department Of Transport;

MARPOL: The International Convention for Prevention of Marine Pollution For Ships

IMDG: International Maritime Dangerous Goods;

RID: Regulations concerning the International Transport of Dangerous Goods by Rail;

ADR: European Agreement concerning the International Carriage of Dangerous Goods

by Road;

ICAO: International Civil Aviation Organization

PBT: Persistent, bioaccumulative and toxic substances

vPvB: Very persistent and very bioaccumulative substances

Prepared by safety and environment affairs.

Date of issue: 10.04.24 Version: 3.0

This SDS covers the product under the name of Alucem-HT2 Adhesive Cement. The information is based on the current state of our knowledge and relates to the product in its condition as applied. However, no guarantee, warranty or assurance is accepted either explicitly or implicitly for the accuracy, reliability and/or completeness of this information.

We expressly call on the person receiving this information to check on the suitability and completeness of this information for their particular application.